

CABLE TERMINATION

Ring and fork terminals

Pre-insulated crimp terminals, colour-coded by wire size

Tin-plated copper terminals with vinyl insulation and a flared barrel for easy wire entry. Low insertion force and easy crimping give a secure termination every time.



Tin-plated copper

Copper body with tin plating for conductivity and corrosion resistance.

Colour-coded

Red 0.5-1.5mm², blue 1.5-2.5mm², yellow 4-6mm².

Rated to 600V

Maximum current: red 19A, blue 27A, yellow 48A.

-10°C to +75°C

Flared barrel

RoHS and REACH compliant

Range

EW code	Type	Colour	Wire range	Stud	Length
104940	Ring	Red	0.5 - 1.5mm ²	M4	19.4mm
104941	Ring	Red	0.5 - 1.5mm ²	M5	20.8mm
101456	Ring	Blue	1.5 - 2.5mm ²	M5	21.8mm
101457	Ring	Blue	1.5 - 2.5mm ²	M6	26.8mm
106197	Ring	Yellow	4.0 - 6.0mm ²	M5	27.3mm
106198	Ring	Yellow	4.0 - 6.0mm ²	M6	29.5mm
106199	Ring	Yellow	4.0 - 6.0mm ²	M8	34.5mm
125451	Ring	Yellow	4.0 - 6.0mm ²	M10	34.5mm
106195	Ring	Yellow	4.0 - 6.0mm ²	M12	39.1mm
104945	Fork	Red	0.5 - 1.5mm ²	M4	21.0mm

Order by 1pm for next-day UK delivery, or collect from Bristol or London. Quotes back within an hour. Trade only.